



## HAV Series



### Features

- High quality machined cast PMMA body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale
- Adjustable flow control valve

### Specifications

- Max. operating pressure ..... 85 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration media ..... air
- Accuracy of full scale flow ..... ±4%

Model	l/min (Air)	BSP Connector	Pressure (psi)
HAV-1	0.1 ~ 1	1/4" quick tube	85
HAV-2	0.2 ~ 2	1/4" quick tube	85
HAV-3	0.25 ~ 2.5	1/4" quick tube	85
HAV-4	0.6 ~ 6	1/4" quick tube	85
HAV-5	1 ~ 4	1/4" quick tube	85
HAV-6	1 ~ 10	1/4" quick tube	85
HAV-7	1 ~ 12	1/4" quick tube	85
HAV-8	0.1 ~ 0.8	1/4"	85
HAV-9	0.1 ~ 1.5	1/4"	85
HAV-10	0.3 ~ 3	1/4"	85
HAV-11	0.4 ~ 4	1/4" tube	85
HAV-12	0.5 ~ 8	1/4"	85
HAV-13	1 ~ 5	1/4"	85
HAV-14	1 ~ 12	1/4"	85
HAV-15	2 ~ 10	1/4"	85
HAV-16	3 ~ 15	1/4"	85
HAV-17	2 ~ 20	1/4"	85
HAV-18	5 ~ 25	1/4"	85
HAV-19	3 ~ 30	1/4"	85
HAV-20	10 ~ 60	1/4"	85
HAV-21	20 ~ 70	1/4"	85
HAV-22	0.05 ~ 0.25 m <sup>3</sup> /h	1/4"	85
HAV-23	0.04 ~ 0.4 m <sup>3</sup> /h	1/4"	85
HAV-24	0.16 ~ 1.6 m <sup>3</sup> /h	1/4"	85
HAV-25	0.1 ~ 1 m <sup>3</sup> /h	1/4"	85
HAV-26	0.2 ~ 2 m <sup>3</sup> /h	1/4"	85



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com