



HPV Series



Features

- High quality machined cast PMMA body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale
- Come with adjustable flow control valve

Specifications

- Max. operating pressure 85 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration liquid water (S.G. 1)
- Accuracy of full scale flow $\pm 4\%$

Model	U. S. GPM	LPM	BSP (M) Connector	Pressure (psi)
HPV-1		15 ~ 150 LPH	1/2"	85
HPV-2		10 ~ 100 LPH	1/2"	85
HPV-3		16 ~ 160 LPH	1/2"	85
HPV-4		25 ~ 250 LPH	1/2"	85
HPV-5	0.1 ~ 1	0.5 ~ 4	3/4"	85
HPV-6	0.2 ~ 2	1 ~ 17	3/4"	85
HPV-7	0.3 ~ 3	1 ~ 11	1"	85
HPV-8	0.5 ~ 5	2 ~ 18	1"	85
HPV-9	2 ~ 10	10 ~ 35	1"	85
HPV-10	4 ~ 14	15 ~ 50	1"	85
HPV-11	6 ~ 20	20 ~ 70	1"	85
HPV-12	10 ~ 35	30 ~ 130	1"	85
HPV-13	10 ~ 40	30 ~ 150	1"	85
HPV-14	15 ~ 45	50 ~ 170	1"	85

