



HLM Series



Features

- High quality machined cast P.C. body
- Highly polished, one piece body
- Sturdy ABS connectors, ABS float
- Union ends simplify installation and maintenance
- Direct reading permanent scale

Specifications

- Max. operating pressure 85 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration liquid water (S.G. 1)
- Accuracy of full scale flow $\pm 4\%$

Model	Flow Rate m ³ /hr	Length (mm)	Socket Connector	Pressure (psi)
HLM-1	0.04 ~ 0.4	195	1/2"	85
HLM-2	0.06 ~ 0.6	195	1/2"	85
HLM-3	0.1 ~ 1.0	195	1/2"	85
HLM-4	0.16 ~ 1.6	228	1"	85
HLM-5	0.25 ~ 2.5	228	1"	85
HLM-6	0.4 ~ 4	290	1 1/2"	85
HLM-7	0.6 ~ 6	290	1 1/2"	85
HLM-8	1.0 ~ 10	350	2"	85
HLM-9	1.6 ~ 16	350	2"	85
HLM-10	5.0 ~ 25	430	2 1/2"	85
HLM-11	8.0 ~ 40	430	2 1/2"	85
HLM-12	12 ~ 60	430	2 1/2"	85
HLM-13	16 ~ 90	550	3 1/2"	85
HLM-14	18 ~ 120	550	3 1/2"	85
HLM-15	25 ~ 150	550	4 1/2"	85
HLM-16	25 ~ 180	550	4 1/2"	85



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com