



HP Series



Features

- High quality machined cast PMMA body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale

Specifications

- Max. operating pressure 150 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration liquid water (S.G. 1)
- Accuracy of full scale flow $\pm 4\%$

Model	U. S. GPM	LPM	BSPT (M) Connector	Pressure (psi)
HP-M1	0.05 ~ 0.5	0.2 ~ 2	1/2"	150
HP-0	0.1 ~ 1	0.5 ~ 4	1/2"	150
HP-1	0.2 ~ 2	0.8 ~ 8	1/2"	150
HP-2	0.5 ~ 5	1.8 ~ 18	1/2"	150
HP-3	2 ~ 10	8 ~ 40	3/4"	150
HP-4	2 ~ 16	4 ~ 60	3/4"	150
HP-5	4 ~ 24	10 ~ 100	1"	150
HP-6	5 ~ 35	10 ~ 130	1"	150
HP-7	5 ~ 40	10 ~ 150	1"	150
HP-8	5 ~ 45	10 ~ 170	1"	150
HP-9	10 ~ 50	60 ~ 200	1.5"	150
HP-10	10 ~ 60	60 ~ 240	1.5"	150
HP-11	20 ~ 70	60 ~ 260	1.5"	150
HP-12	20 ~ 80	60 ~ 300	1.5"	150



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com