



HPG Series



Features

- High quality machined cast PMMA body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale

Specifications

- Max. operating pressure 150 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration media air
- Accuracy of full scale flow $\pm 4\%$

Model	Nm ³ /hr (Air)	BSPT (M) Connector	Pressure (psi)
HPG-1	0.01 ~ 0.1	1/2"	150
HPG-2	0.04 ~ 0.4	1/2"	150
HPG-3	0.1 ~ 1	1/2"	150
HPG-4	0.16 ~ 1.6	1/2"	150
HPG-5	0.24 ~ 3	1/2"	150
HPG-6	0.4 ~ 4	1/2"	150
HPG-7	0.6 ~ 6	1/2"	150
HPG-8	0.8 ~ 8	1/2"	150
HPG-9	1 ~ 10	1/2"	150
HPG-10	1.6 ~ 16	1/2"	150
HPG-11	2 ~ 20	1/2"	150
HPG-12	2.5 ~ 25	1/2"	150
HPG-13	3 ~ 30	1/2"	150
HPG-14	4 ~ 40	1/2"	150
HPG-15	6 ~ 60	1"	150
HPG-16	10 ~ 100	1"	150
HPG-17	16 ~ 160	1"	150
HPG-18	20 ~ 200	1"	150
HPG-19	25 ~ 250	1"	150
HPG-20	30 ~ 300	1"	150
HPG-21	35 ~ 350	1"	150



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com