



HPZ Series



Features

- High quality machined cast acrylic body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale

Specifications

- Max. operating pressure 85 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration liquid water (S.G. 1)
- Accuracy of full scale flow $\pm 4\%$

Model	U. S. GPM	LPM	BSP Connector	Pressure (psi)
HPZ-1	0.02 ~ 0.2	4 ~ 40LPH	1/2" (F)	85
HPZ-2	0.1 ~ 1	0.5 ~ 4	1/2" (F)	85
HPZ-3	0.2 ~ 2	1 ~ 7	1/2" (F)	85
HPZ-4	0.5 ~ 5	1.8 ~ 18	1/2" (F)	85
HPZ-5	1.5 ~ 9	400 ~ 2000LPH	1/2" (F)	85
HPZ-6	1 ~ 10	4 ~ 36	1" (F)	85
HPZ-7	1 ~ 15	5 ~ 60	1" (F)	85
HPZ-8	2 ~ 20	10 ~ 70	1" (F)	85
HPZ-9	5 ~ 30	20 ~ 100	1" (F)	85
HPZ-10	5 ~ 40	20 ~ 150	1" (F)	85
HPZ-11	5 ~ 45	20 ~ 170	1" (F)	85
HPZ-12	20 ~ 60	80 ~ 220	1" (F)	85
HPZ-13	20 ~ 80	80 ~ 300	2" (F)	85
HPZ-14	20 ~ 100	80 ~ 360	2" (F)	85
HPZ-15	40 ~ 120	150 ~ 450	2" (F)	85
HPZ-16	50 ~ 150	190 ~ 560	2" (F)	85
HPZ-17	60 ~ 200	220 ~ 750	2" (F)	85
HPZ-18	120 ~ 300	450 ~ 1100	3" (F)	85



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com