



## HTT Series



### Features

- High quality borosilicate glass tube
- Highly polished, one piece body
- Sturdy teflon coated flange connections
- Teflon coated float
- Direct reading permanent scale
- Excellence in corrosion resistance

### Specifications

- Max. operating pressure ..... 85 psi
- Max. operating temperature ... 180 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration liquid ..... water (S.G. 1)
- Accuracy of full scale flow .... ± 4%

HTT series - Teflon (PTFE) coated guide rod, float and other wetted part

Model	LPH	Flange Connection	Pressure (psi)
HTT - 1	16 ~ 160	1/2"	85
HTT - 2	25 ~ 250	1/2"	85
HTT - 3	40 ~ 400	1/2"	85
HTT - 4	60 ~ 600	1"	85
HTT - 5	100 ~ 1000	1"	85
HTT - 6	160 ~ 1600	1 1/2"	85
HTT - 7	250 ~ 2500	1 1/2"	85
HTT - 8	400 ~ 4000	2"	85
HTT - 9	600 ~ 6000	2"	85
HTT - 10	1 ~ 10m <sup>3</sup> /hr	3"	60
HTT - 11	1.6 ~ 16m <sup>3</sup> /hr	3"	60
HTT - 12	5 ~ 25m <sup>3</sup> /hr	4"	60
HTT - 13	8 ~ 40m <sup>3</sup> /hr	4"	60

