



HTTG Series



Features

- High quality borosilicate glass tube
- Highly polished, one piece body
- Sturdy teflon coated flange connections
- Teflon coated float
- Direct reading permanent scale
- Excellence in corrosion resistance

Specifications

- Max. operating pressure 85 psi
- Max. operating temperature ... 180 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration media air
- Accuracy of full scale flow ± 4%

HTTG series - Teflon (PTFE) coated guide rod, float and other wetted part

Model	Nm ³ /hr (Air)	Flange Connection	Pressure (psi)
HTTG - 1	0.25 ~ 2.5	1/2"	85
HTTG - 2	0.4 ~ 4	1/2"	85
HTTG - 3	0.6 ~ 6	1/2"	85
HTTG - 4	1 ~ 10	1"	85
HTTG - 5	1.6 ~ 16	1"	85
HTTG - 6	2.5 ~ 25	1 1/2"	85
HTTG - 7	4 ~ 40	1 1/2"	85
HTTG - 8	6 ~ 60	2"	85
HTTG - 9	10 ~ 100	2"	85
HTTG - 10	16 ~ 160	3"	60
HTTG - 11	50 ~ 250	3"	60
HTTG - 12	80 ~ 400	4"	60
HTTG - 13	120 ~ 600	4"	60
HTTG - 14	200 ~ 1000	4"	60



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com